# LEDcure VZ - Aircooled



VZ LEDcure is specifically designed for the needs of the Super Wide and Grand Format Printing industry with 16W/cm² output, and 20% more dose than it's sister product the SZ LEDcure. Over the years the SubZero and VZero products have been established as some of the world's leading UV curing systems for inkjet applications. Now Integration Technology is introducing the next generation of the family; VZ LEDcure.

The Research and Development team at ITL have used all of the proven features and benefits of their existing LED systems and refined them to new levels in a market leading new air-cooled UV LED Curing device. When compared to the older generation of LED systems, remarkable progress has been made in the drying performance of VZ LEDcure.

By combining and integrating ITL's latest XT8 high efficiency array and VARIcool technologies, the VZ LEDcure enables users to achieve higher efficiency and more output in terms of both intensity and dose.

## **High-performance LEDs**

VZ LEDcure is ready to use immediately after switch on, there is no warm-up or cooling times, which saves both time and energy. LEDs have a long service life of greater than 20,000 hours, and in addition modules in the VZ LEDcure can be easily replaced if required for either upgrade or servicing. Available wavelengths: standard 395nm, or alternative wavelengths of 365nm, 385nm, 405nm, or mixed wavelength arrays are available on request.

# Warranty

Integration Technology grants a warranty of five years on each XT8 LED module. Older systems can also be upgraded with the XT8 technology, then this warranty also applies to those modules.

New UV LED systems from ITL are all fitted with the innovative XT8 boost technology as standard.






#### XT8: UV LED Booster

With XT8 UV LED Booster technology, the system reaches an extremely high output and dose which greatly increases cure speeds offering customers a wider choice in all applications. An extended service life is achieved since the semi-conductor chips are not being driven as hard when compared to other products on the market. The 30% boost in efficiency is available for systems fitted with 365, 385, 395 or 405nm or mixed wavelength arrays, first introduced by ITL in 2010.



## VARIcool Technology:

The VARIcool controls the cooling according to ambient temperatures delivering a consistent output in all working environments while minimising the noise and turbulence normally associated with fan cooling.



**VZ LEDcure head input voltage:** 48 v.d.c.

**Operating temperature:** <40°C **Noise:** decreased noise by VARIcool

**Cable length:** 8 m (High Flex) for drag chain standard (alternative lengths available)

Dimensions of LED head: Width 70mm x Height 202mm; Emmitting Window: Width 20 mm

VZ LEDcure is designed as LED head only option. Integration Technology will provide all relevant protocol information required and support potential clients with furnishing their own power supply units. Alternatively the VZ LEDcure can be supplied as fully configured package including cables and power supply.

\* 395nm at the emmitting window using an EIT Power Map UVV sensor

Head Office: Integration Technology Ltd., Heyford Park, Upper Heyford, Oxfordshire, OX25 5HA, United Kingdom Tel.: +44 [0] 1869 233611, Fax: +44 [0] 1869 233599, mail@uvintegration.com

Integration Technology North America dbohn@uvintegration.com Integration Technology Korea jyoon@uvintegration.com Integration Technology (China) Ltd. syang@uvintegration.com Integration Technology
Japan
ykatsuta@uvintegration.com

Integration Technology Latin America edsel@uvintegration.com.br

<sup>\*\*</sup> Addressability patented by European patent: EP1599340/ GB2399162, Cross licence with Lumen Dynamics Group Inc. U.S. Patent No. 6,683,421